



## 106.HTH



The 106.HTH provides an unbeatable combination of excellent sound quality, output-per-size and comprehensive direct-weather performance.



**Cena:**

**Kategorie:** [Audio](#), [Scena](#), [Głośniki](#), [Instalacje AV](#),  
[Nagłośnienie obiektów](#)

### GALLERY IMAGES



### OPIS

The 106.HTH can be used anywhere outdoors - including on ships or near ocean applications. Unlike typical small-format speakers, the 106.HTH is equipped with a small-format compression driver coupled to a 110 x 70-degree constant-directivity horn. This horn / driver delivers excellent vocal intelligibility, smooth response and good coverage. Its 6.5" woofer features a large-sized 1.75" voice coil for extended bandwidth and power handling without

needing performance-degrading passive protection. The system's 316 marine-grade stainless steel U-Bracket, enclosure reinforcements and its HYBRID stainless steel grille with marine-capable coating ensure extraordinary corrosion resistance and long life. The 106.HTH is a high performance solution for demanding applications where space is limited. It can be powered Lo-Z (8 ohm) or Hi-Z (70.7 – 100 volts with taps at 50, 25 and 12.5 watts). The impedance selection is made using separate barrier strips for low and high impedance connections, which provides better reliability than switches.

**Mounting U-Bracket is included** - 316 marine grade stainless steel

#### SPECIFICATIONS

- Frequency Response: 80Hz – 20,000Hz
- Coverage Pattern: 110 H X 70 V
- Crossover Frequency: 3000 Hz
- System Sensitivity (1 Watt / 1 Meter): 89dB
- Power Handling: 100 watts continuous 200 watts program 400 watts peak
- Input Impedance (Lo Z):8-ohms
- Input Taps (Hi Z):50 Watts, 25 Watts, 12.5 Watts
- Weight:6.5kg (14.6 lb.)
- Dimensions (H x W x D) mm: 312 x 185 x 217.1
- Dimensions (H x W x D) in: 12.3 x 7.3 x 8.5