108.HTH

The 108.HTH provides a unique combination of excellent performance, direct weather capability and amazing flexibility. The 108.HTH includes a long-throw 60 x 40-degree rotatable horn that's factory installed, but also includes a rotatable wide-throw 105 x 60-degree horn too.



Cena:
Kategorie: Audio, Scena, Głośniki, Instalacje AV, Nagłośnienie obiektów



GALLERY IMAGES











OPIS

108.HTH PLATINUM HYBRID SERIES LOUDSPEAKERS

The 108.HTH's rotatable long or wide-throw horns, its wide, smooth response and beefy components provide excellent performance for a variety of applications. Its built-in 3-tap transformer provide 70.7 - 100 volt taps at 150, 75 and 37.5 watts or it can be powered as a low-impedance system. The 108.HTH's multiple 316 marine stainless steel suspension points and range of installation hardware add to its already impressive flexibility. The 108.HTH is designed and built tough enough to handle any outdoor application, but is widely used for indoor applications too thanks to its high performance and flexibility.

Mounting options sold separately

SPECIFICATIONS

- Frequency Response: 65Hz – 16,000Hz
- Coverage Pattern: 60 x 40 degrees or 105 x 60 degrees
- Crossover Frequency: 2000 Hz (60 x 40 horn)1600 Hz (105 x 60 horn)
- System Sensitivity (1 Watt / 1 Meter): 92dB
- Power Handling: 200 watts continuous 400 watts program 800 watts peak

- Input Impedance (Lo Z): 8-ohms
- Input Taps (Hi Z):150 watts, 75 watts, 37.5 watts
- Weight:16.5 kg (36.4 lb.)
- Dimensions (H x W x D) mm: 483.3 x 243.2 x 270.8
- Dimensions (H x W x D) in: 19.05 x 9.56 x 10.6