112.HTH

The 112.HTH provides highly intelligible vocals, extended low-frequency response and high output capability from a reasonably-sized direct weather capable system.



Cena:
Kategorie: Audio, Scena, Głośniki, Instalacje AV, Nagłośnienie obiektów



GALLERY IMAGES





OPIS

112.HTH PLATINUM HYBRID SERIES LOUDSPEAKERS

The 112.HTH can be used anywhere outdoors thanks to its combination of 316 marine stainless steel suspension hardware and enclosure reinforcements, HYBRID stainless steel grille with marine capable coating and tough UV-resistant enclosure. The 112.HTH comes with a large-sized, rotatable 60 x 40-degree horn installed, but a rotatable 105 x 60-degree for wide coverage applications is also available with order. The 112.HTH can be powered as a low impedance system (800 watts continuous, 3,200 watts peak at 8 ohms) or as a high impedance system (70.7 – 100 volts with taps at 150 watts, 75 watts and 37.5 watts). The 112.HTH delivers top-class performance, impressive flexibility and long useful life. Its highly defined audio performance and output capability make it a solution for indoor or outdoor audio applications.

Mounting options sold separately

SPECIFICATIONS

- Frequency Response: 60Hz – 16,000Hz
- Coverage Pattern: ET-60/40, 60 x 40 degrees, ET-105/60, 105 x 60 degrees
- Crossover Frequency: 1800 Hz (60 x 40 horn); 1300 Hz (105 x 60 horn
- System Sensitivity (1 Watt / 1 Meter): 96dB
- Power Handling: 800 watts continuous; 1600 watts program; 3200 watts peak
- Input Impedance (Lo Z): 8-ohms
- Input Taps (Hi Z): 150 watts, 75 watts, 37.5 watts
- Weight: 35.3kg (77.8 lb.)
- Dimensions (H x W x D) mm: 748 x 368 x 398.3
- Dimensions (H x W x D) in: 29.5 x 14.5 x 15.7