AI 81

×

The **Ai81** is a 2-way passive ultra-slim column loudspeaker specifically designed to ensure a **minimal-discreet visual impact** and an elegant design for an easy and seamlessly layout integration while ensuring the sound quality for which **Outline** has always been recognized.



This tiny, modular, externally powered loudspeaker provides the best performance when installed on a flat surface. It features eight **1.3" neodymium magnet driver** and one **0.7" treated silk dome tweeter** producing a wide nominal dispersion and a maximum SPL peak of 112 dB.

With a nominal impedance of **16 ohms** and requiring only one single channel, it is possible to deploy up to eight Ai81 with just one single amplification channel on a parallel cost-saving installation solution.

Also, a **passive crossover** (manufactured with top-grade components) takes care to split the LF and HF and provides single and double protection for the drivers (LF and HF respectively).

All the above enclosed in a compact, refined and elegant design weighting just **0.85 kg** (1.85 lb).

The cabinet, in **HCDF** (Hydrophobic Compact Density Fiber), is coated with polyurethane paint ensuring the correct operation even in the toughest places; while the grill, made of galvanized steel, features an epoxy powder coating. Custom RAL colour options are available to perfectly match any architectural layout.

PERFORMANCE SPECIFICATIONS

Frequency Response (-10 dB) Horizontal Dispersion	300 Hz – 20 kHz 160°
Vertical Dispersion	40°
Impedance (Nom / Min)	16 Ω / 16.6 Ω
Watt AES (Peak) *	320 W
Maximum SPL Output **	112 dB SPL
	* according to AES2-2012 (+12 dB) standard ** calculated using +12 dB Crest Factor signal (AES2-2012), Half space

PHYSICAL

Component Low	8 x 1.3" NdFeB Full Range driver
Component High	0.7" treated silk dome tweeter
Connector	2-pin Euroblock
Cabinet Material	HCDF (Hydrophobic Compact Density Fiber)

	The first sector
Cabinet	FINISN
Cabinee	

Grill Installation points

Height Width Depth Weight

Black or White textured polyurethane paint
(overpainted RAL colors on request)
Epoxy powder coated
2 through holes diam. 4 mm on front / 3 x M5 on
back
570 mm – 22 4/8"
46 mm – 1 6/8"
25 mm – 1"
0.85 kg – 1.85 lb