

## AS 6



**AS6** subwoofer system has been specifically designed to extend the architectural series low-end. Featuring high-grade components and the same research for detail and design that distinguishes this series, the AS6 ensures equal tonal balance and voicing and delivers deep and agile, pristine bass-end whether used in as home cinema or a stereo system.



**Cena:**

**Kategorie:** [Audio](#), [Scena](#), [Głośniki](#), [Instalacje AV](#),  
[Nagłośnienie obiektów](#)

## GALLERY IMAGES



## OPIS

Its design features a **6" high-power woofer** and a **passive radiator** (114 dB max SPL down to 42 Hz), offering the advantage of being able to faithfully reproduce the lowest frequencies while keeping an ultra-low-profile dimension to match any architectural need. The subwoofer can be used either floor standing or suspended with a dedicated bracket (sold separately), providing the AS6 with an even more versatile installation option.

Made of **HCDF** (Hydrophobic Compact Density Fiber), by default it is coated with black or white textured polyurethane paint that ensures toughest places operation and a very stylish and discreet look. While the grill, made of galvanised steel, features an epoxy powder coating to protect the front of the loudspeaker.

Additionally, custom RAL colour options are available for perfect and seamless integration with any venue layout.

---

## PERFORMANCE SPECIFICATIONS

Frequency Response (-10 dB)	42 Hz – 350 Hz
Nominal Dispersion	Quasi-omnidirectional
Impedance (Nom / Min)	8 Ω / 8.6 Ω
Watt AES (Continuous / Peak) *	150 / 1500 W
Maximum SPL Output **	114 dB SPL
	* according to AES2-2012 (+12 dB) standard
	** <i>calculated using +12 dB Crest Factor signal (AES2-2012), Half space</i>

## PHYSICAL

Components	6" woofer + 6" passive radiator
Connector	4-pin Euroblock
Cabinet Material	HCDF (Hydrophobic Compact Density Fiber)
Cabinet Finish	Black or White textured polyurethane paint (overpainted RAL colors on request)
Grill	Epoxy powder coated steel grill
Installation points	2 x M6
Height	200 mm – 7 7/8"
Width	450 mm – 17 6/8"
Depth	120 mm – 4 6/8"
Weight	6.5 kg – 14.3 lb

