C10


The DUAL C10 is a trapezoidal-wedged shape multipurpose speaker for use in PA systems or as an on-stage monitor that features a 10" low frequency transducer of 2 in VC capable of delivering excellent dynamic range, flat frequency response and a very low distortion figure which combined with 1" (1.73in VC) HF driver result in a
superb sound and exceptional performance.



Cena:
Kategorie: Audio, Scena, Głośniki, Instalacje AV, Nagłośnienie obiektów



GALLERY IMAGES



OPIS

Key Features

- Multipurpose 2-way passive speaker
- Bass reflex trapezoidal enclosure
- 10" (2in VC) MF + 1" (1.73in VC) HF EU transducers
- 2x NL4 connected in parallel

- User-rotatable CD horn 90°x60° for ideal dispersion
- Ø35mm pole mount with 0° and 5° tilt
- Integrated rigging system with 3x M10 inserts
- Rugged and durable 15mm birch plywood
- Powder coated custom perforated steel grille

TECH SPECS

Type	2-Way passive loudspeaker
Enclosure Design	Bass reflex trapezoidal
Power Output (RMS)	360W (EMS) 510W (Program) 900W (Peak)
Frequency Range	75Hz - 18kHz
Nominal Impedance	8Ohm
Transducer Type	10" MF (2in VC) EU transducer 1" HF (1.73in VC) EU transducer
Dispersion	CD horn, 90°x60° and 60°x90° User-rotatable
Crossover Frequency	2000Hz
Max. SPL (peak)	125dB @ 1m
Connector	2x NL4 in parallel
Construction	15mm birch plywood, textured polyurea coating
Grille	Custom perforated metal grille with acoustic foam
Installation / Rigging / Flying	Ø35mm pole mount with 0° and 5° tilt 3x M8 flying points "U" bracket for horizontal and vertical installation
Dimensions (WxDxH)	320x350x550mm 12.60x13.78x21.65in
Weight	18Kg 39.68lb