



## C3 3" MICRO PENDANT SPEAKER



C3 3" Micro Ceiling Speaker with Pendant Cover Kit, Speaker Wire, and Integrated Safety Cable



**Cena:**

**Kategorie:** [Audio](#), [Instalacje AV](#), [Nagłośnienie kinowe](#),  
[Nagłośnienie obiektów](#)

### GALLERY IMAGES



### OPIS

The Pure Resonance Audio C3 3" pendant speaker features a stylish and intelligent design blending seamlessly into exposed open plenum ceilings, raked ceilings, and other contemporary open architectural designs. With 8 Ohm and commercial 70 Volt audio taps and integrated single point mount, the C3 pendant speaker is excellent for sound masking, background music, and paging creating the perfect atmosphere in offices, restaurants, retail

stores, resort and hospitality venues, or any other open-architecture high ceiling environments, and other spaces where hanging pendant speakers are required.

## **CLEAR WIDE-COVERAGE**

The down-firing design of the 3" driver directs the high fidelity sound for wide evenly distributed coverage.

## **Sleek Modern Design**

The C3 pendant speaker offers a very contemporary and stylish design that's aesthetically pleasing in any space.

## **Easy Install**

Simply connect the wire and safety cable combo to the back of the C3 ceiling speaker, thread the wire through the pendant mount cylinder, and twist in the C3 speaker. The wire length can easily be modified for suspension from the desired ceiling point.

## **Open Ceilings**

Ideal for exposed structure or open plenum ceiling venues where a stylish contemporary speaker coordinates well with the architectural design.

## **Hardware Included**

The included 12ft of 2 conductor 20 gauge speaker cable contains an integrated multi-strand steel stress-relief safety cable and loop nut cinch for quick installation.

## **MULTI-FUNCTION**

Ideal for sound masking, paging, and background or foreground music in restaurants, retail stores, offices, or any other open-architecture high ceiling environments.

---

## C3 3" Pendant Speaker

The Pure Resonance Audio C3 3" pendant speaker kit features a stylish and intelligent design ideal for exposed structures or open plenum ceilings. The C3 pendant speaker system delivers superb sound masking, background music, and paging in offices, restaurants, retail stores, resort and hospitality venues, or any other open-architecture high ceiling environments, and other spaces where hanging pendant speakers are required.

With 8 Ohm and commercial 70 Volt audio taps and integrated single point mount, the C3 speaker is designed to provide excellent sound quality for a wide variety of business music sound system applications such as background music, paging, and sound masking. Compact and lightweight, the Pure Resonance Audio C3 3" Micro speaker fits beautifully into the pendant cover kit and produces quality sound and excellent dispersion of both music and vocals. Because of its small size, the C3 speaker is great for installations where architectural or aesthetic considerations require a small format pendant speaker.

The C3 pendant-mount hanging kit is a quick and easy turn-key installation solution. The C3 ceiling speaker simply twists into the pendant cylinder. The switch on the back of the C3 provides wattage and loudness control for even sound distribution. Included is a 2 conductor 20 gauge speaker cable containing an integrated 12-foot multi-strand steel stress-relief safety cable and loop-nut safety cinch. The wire length can easily be modified for single-point suspension mounting from the desired structurally adequate ceiling points (consult your architect or engineer).

---

## SPECIFICATIONS

**Frequency Response:** 120Hz - 20kHz

**Low Frequency (-10 dB):** 180 Hz - 20 kHz

**Impedance:** 8 Ohms with 70V transformer (built-in)

**Maximum Input Voltage:** 17 dBV (7.1V, 6W into 8Ω)

**Power Taps @ 70V:** 1.5W / 3W / 5W

**Power Taps @ 100V:** 3W / 6W / 10W

**Transducer:** Full-range 3" driver

**Nominal Coverage Angle:** 130° Conical Coverage

**180° Coverage Angle:**

-1 dB @ 1.25 kHz

-5 dB @ 2.5 kHz

**140° Coverage Angle:** -10 dB @ 10 kHz

**Sensitivity SPL:** 85 dB @ 1W/1 m

**Maximum SPL:** 89.6 dB referenced @ 1m

**Wire with Safety Cable:** 12' (3.6 m)

**Height:** 7" (177.8 mm)

**Height with Nut:** 7.125" (180.975 mm)

**Front:** 4.75" (120.65 mm)

**Rear:** 3.125" (79.375 mm)

**Net Weight:** 2.7 lbs (1.225 kg)