CX12

This SOUL CX12 monitor is equipped with an European transducer having the LF element a 4in voice coil combined with the HF 2.9in voice coil matching the curvilinear profile LF cone that provides smooth response within its intended frequency range and the integrated HF compression driver that has been designed to give smooth coherent wave front in the horn entrance in all working frequency range for a surprising performance.



Cena:
Kategorie: Audio, Scena, Głośniki, Instalacje AV, Nagłośnienie obiektów



GALLERY IMAGES







OPIS

Key Features

- Professional coaxial stage monitor
- 2-way passive version
- 12" LF (4in) + 2.9" HF voice coil European transducers
- Faithful dynamic response and great range

- Connector plate on the bottom with 2x Speakon NL4®
- Integrated Ø35mm pole mount
- Rugged and durable 15mm birch plywood construction
- Powder coated custom perforated steel grille

Tech Spec

Type	Coaxial stage monitor - passive
Enclosure Design	Bass reflex
Power Output (RMS)	400W / 80W (AES) 800W / 160W (Program) 1600W (Peak)
Frequency Range	80Hz - 20kHz
Nominal Impedance	8ohm
Transducer Type	12" coaxial EU transducer LF 4in VC + HF 2.9in VC
Dispersion	80° Axisymmetrical (conical)
Crossover Frequency	1500Hz
Max. SPL (peak)	124dB @ 1m
Connector	2x Neutrik® NL4 in parallel
Construction	15mm birch plywood, textured polyurea coating
Grille	Custom perforated metal grille w/ acoustic foam
Installation / Rigging / Flying	4 rubber feet Ø35mm pole mount socket
Dimensions (WxDxH)	510x540x360mm 20.08x21.26x14.17in
Weight	25Kg 55.16lb