D6K4



Cena:
Kategorie: Audio, Scena, Wzmacniacze mocy, Instalacje AV, Wzmacniacze mocy i procesory DSP



GALLERY IMAGES





OPIS

Key Features

- Professional and powerful class D amp
- High dynamic range and low distortion
- 4x 1600W / 4ohm high power channels
- 2x 3200W / 8ohm BRIDGE
- Status LEDs in front panel
- Electronically balanced XLR inputs, Speakon outputs
- Efficient forced-air cooling system
- Fully self-protected for SMPS and channels
- AC 100V - 240V, 50/60Hz Universal mains
- Solid construction for 19” - 2U rack mount

TECH SPECS

Type	Class D amplifier, Powersoft modules

No. of Channels	4
RMS Power @ 8Ω / 1kHz / 0.1% THD	2x 3200W - BRIDGE
RMS Power @ 4Ω / 1kHz / 0.1% THD	4x 1600W
Gain	32dB (x80 voltage gain)
Signal-to-noise ratio	115dB (A weighted)
T.H.D. (20Hz - 20kHz)	< 0,05% from 0.1W to full power
Other Features	Output voltage: 150peak Output current: 54Apeak
Frequency Range	10Hz - 25kHz (±3dB) @ 1W, 4ohm
Damping Factor	> 1000 @ 100Hz
Inputs	4x XLR/F 3p
Outputs	4x XLR/M 3p - LINK 4x Speakon NL4 2x Speakon NL4 red - Bridge
Indicators	Status, Clip, Protect, Bridge
Cooling	Fan, variable speed, temperature controlled
Protections	Extensive protection circuitry: power limiters, thermmal shutdown Short circuit, overload and clip limiter Temperature protection of transformer & heat-sinks
Power Consumption	Regulated SMPS with PFC
Operation Voltage	AC 100V - 240V, 50/60Hz
Connectors	Neutrik powerCON in
Other Features	Rugged and solid steel construction, AL front panel
Other Features	Electrostatic black powder coating
Dimensions (WxHxD)	2RU - Rack 19" 320mm depth
Weight	11Kg 24.25lb