



DIMMER D1216



Cena:

Kategorie: [Audio](#), [Scena](#), [Wzmacniacze mocy](#), [Instalacje AV](#),
[Wzmacniacze mocy i procesory DSP](#)

GALLERY IMAGES



OPIS

Key Features

- Triac Dimmerpack
- 12-channel version (3000W per channel)
- 16 Amp circuit breakers on each channel
- DMX 512 and analog (DC 0-10 V) signal input
- Preheat rotative control (all channels) up to 50% output level
- DMX start address configurable with rotative switches
- Multiple output connector types (shuko, terminal and 16-pole harting)

- High quality inductors and filtering circuits
- Solid construction for 19" rack - 3U mounting

Tech Spec

Type	Triac Dimmerpack
No. of Channels	12
Power Output (W)	3000
Channel Output Rating	16 Amps
Load Type	Resistive and inductive
Output Connector (S - Shuko)	Yes
Output Connector (T - Terminal)	Yes
Output Connector (H - Harting 16)	Yes
Channel MCB Type	1 pole
Current Control Technology	Triac phase-controlled
Indicators	DMX status, Phase status, Active outputs
Inputs	DMX (XLR 3p), Analog (D15)
Outputs	DMX (XLR 3P)
Features	DMX patch addresser, Pre-heat
Cooling Fan	Cont. speed fan, 80mm / 230V
Fan Cooling Control	Thermal sensor
Protections	Overload protection by M.C.B.
Operating Voltage	230V AC, 50~60 Hz
Power Consumption	260VA
Dimensions (WxHxD)	3RU spaces, 385mm depth
Weight	13Kg