



DRAGONFLY



The ULTIMATE portable PA system. Light, loud, long battery life, and **weatherproof**. **Half the size and weight** of popular commercial-grade systems. **Up to eight hour full power operation from internal battery**.



Cena:

Kategorie: [Audio](#), [Scena](#), [Głośniki](#), [Instalacje AV](#),
[Nagłośnienie obiektów](#)

GALLERY IMAGES



OPIS

No fragile injection-molded construction, underpowered amplifiers, or heavy lead-acid batteries – the DragonFly redefines what’s possible in a compact all-in-one PA.

The DragonFly gives you the best possible audio in a compact and reliable design that serve for years. **Fully weatherproof**, the DragonFly can easily be transported and set up by one person. As well, a molded in stand-mount socket on the bottom of the unit and inserts on the sides for yoke mounting give the DragonFly a range of deployment options.

FEATURES

- 122dB SPL continuous output
- **Wireless microphone built-in**
- Mixer with **microphone and line level inputs - four total - connect your phone or other audio source**
- **Lightweight- just 24 lbs.**
- **Small**, less than 1 cubic foot
- Fast charging, lightweight LiFePo battery pack
- Fully weatherproof
- **NEW**: switchable **ducking circuit** automatically turns down music when wireless or wired mic is used .
- Can drive 2nd Auxiliary Loudspeaker
- Full Range Neodymium coaxial transducer
- Expansion Slot for Schedulon MP3 player/ recorder, CD player, second wireless microphone or audio distribution module
- Gasketed fold-down cover for mixer control surface
- Integrated smart charger for battery pack – charge and run from 110-240 V AC power, 12-24 V CD power.

OPTIONS

- [Schedulon](#) audio player with auto-play & recording
 - Auxiliary Loudspeaker
 - Audio Distribution Modules: Ethernet Wireless (900Mhz) / Twisted pair
 - All day battery pack (external)
 - Yoke-mount bracket
 - Additional wireless microphone
 - CD player module
-

Physical Specifications

- Height 14.5 in. | 36.8 cm
- Width 8.25 in. | 20.9 cm

- Depth 14 in. | 35.5 cm
- Weight 24 lb. | 10.9 kg

FITTINGS

- Rigging points: 2x 1/4-20 threaded inserts on top (handle mount points)
- Yoke mount points: 2 x 1/4-20 threaded inserts on side
- Standmount socket: 1x 1.5" socket on bottom of unit Handle:
- 1x Strap Handle

Cabinet: LDPE, rotationally Molded Grill: Powder-coated stainless steel

GENERAL SPECIFICATIONS

- Audio Inputs: 1x XLR, mic. level 1x 1/4, line level
 - Audio Outputs: 1x Neutrik NL4MP
 - Amplifier Wattage: 200W RMS into 8 Ohms
 - Power Inputs: AC power (90-240vAC) DC power (12-24vDC)
 - Battery: 5AH NiMH Operational Life: 5 hours full operation 10 hours stand-by
-

AUDIO PERFORMANCE SPECIFICATIONS

- Frequency Response (+/- 2 dB): 90 Hz - 18 kHz M
 - Maximum Output (long term): 121 dB SPL
 - Maximum Output (peak program): 124 dB
 - HF Dispersion: SPL 70°V x 70°H
- Audio specifications based on ALMA EIA 426B test protocols.