G15

This G15 is built on a Reflex Loaded design equipped with a 15" (4in) LF transducer capable of delivering 1200W AES (4800W peak), chosen to provide clean, undistorted low frequency reproduction at very high sound pressure levels and able to withstand high power levels without damage.



Cena:
Kategorie: Audio, Scena, Głośniki, Instalacje AV, Nagłośnienie obiektów



GALLERY IMAGES











OPIS

The BASS series offers a professional and compact passive and active subwoofers range becoming the perfect choice for sound reinforcement challenges demanding high SPL and natural sounding bass response designed to enhance the ultra-low bass of an existing PA system.

Key Features

- Bass reflex subwoofer
- 1x 15" (4in VC) LF EU transducer
- 1200W AES / 7000W Peak power
- 2x NL4 connected in parallel
- Versatile, compact and coherent subwoofer
- Made for an impact bass
- Recesses on the top to facilitate the stacking
- Rugged and durable 18mm birch plywood construction
- Powder coated custom perforated steel grille

TECH SPECS

Type	Compact PASSIVE subwoofer
Enclosure Design	Reflex Loaded
Power Output (RMS)	1200W (AES) 2400W (Program) 7000W (Peak)
Frequency Range	32Hz - 250Hz (-10dB)
Nominal Impedance	8 Ohm
Transducer Type	15" (4in VC) LF EU transducer
Crossover Frequency	N/A

Max. SPL (peak)	126dB @ 1m (continuous) 132dB @ 1m (peak)
Connector	2x NL4 in parallel
Construction	18mm birch plywood with polyurea coating
Grille	Custom perforated metal grille w/ acoustic foam
Installation / Rigging / Flying	4 rubber feet, 2 side handles Ø35mm pole mount socket Prepared for stacking
Dimensions (WxDxH)	590x590x440mm 23.23x23.23x17.32in
Weight	35Kg 77.16lb