



G15A



This G15A is built on a Reflex Loaded design equipped with a 15" (4in) LF transducer capable of delivering 1200W AES (4800W peak), chosen to provide clean, undistorted low frequency reproduction at very high sound pressure levels and able to withstand high power levels without damage.



Cena:

Kategorie: [Audio](#), [Scena](#), [Głośniki](#), [Instalacje AV](#),
[Nagłośnienie obiektów](#)

GALLERY IMAGES



OPIS

The BASS series offers a professional and compact passive and active subwoofers range becoming the perfect choice for sound reinforcement challenges demanding high SPL and natural sounding bass response designed to enhance the ultra-low bass of an existing PA system.

The active version feature a powerful class D single channel amplifier delivering 2400W @

4ohm connected to a fully programmable DSP providing low-ranging yet clearly defined bass response and rendering impulses with great accuracy in a very compact and robust enclosure. The amplifier module is prepared for universal 85- 264Vac mains input and features various electronic protections. To ensure a perfect matching and avoid undesired vibrations during high SPL operation the enclosures are constructed in 18mm reinforced birch plywood with a rugged and durable polyurea coating. The ergonomic carrying handles permit a secure grip from all sides and convenient transport and all models are prepared to accept 4 swivel castors with 16x M6 inserts on the back. Punch and bass sensation do not have to be incompatible factors and this BASS series truly is a great example.

Key Features

- Bass reflex ACTIVE subwoofer
- 1x 15" (4in VC) LF EU transducer
- 1200W AES / 7000W Peak power
- Single channel Class D amplifier with integrated DSP
- Universal 85-264Vac mains, SMPS with PFC
- Versatile, compact and coherent subwoofer
- Made for an impact bass
- Recesses on the top to facilitate the stacking
- Rugged and durable 18mm birch plywood construction
- Powder coated custom perforated steel grille

TECH SPECS

| | |
|--------------------|----------------------------------|
| Type | Compact ACTIVE subwoofer |
| Enclosure Design | Bass reflex |
| Power Output (RMS) | 1200W (AES) |
| | 2400W (Program) |
| | 7000W (Peak) |
| Frequency Range | 32Hz - 250Hz |
| Nominal Impedance | N/A |
| Transducer Type | 1x 15" LF (4in VC) EU transducer |

| | |
|---------------------------------|---|
| Crossover Frequency | DSP controlled with selectable presets 48KHz sampling frequency 24 bit AD/DA converter |
| Max. SPL (peak) | 132dB @ 1m (continuous) |
| Amplifier type | Class D, single channel amplifier |
| Amplifier output | 2400W (continuous) |
| Input | XLR/Jack combo connector |
| Output | XLR/M3p connector |
| Indicators | Power, signal/preset, clip |
| Controls | Master level control, 4 selectable presets |
| Feature | Cooling by convection |
| AC Power Supply | Switching power supply, 85-264Vac |
| AC mains connector | Neutrik® powerCON, Power-in (blue) / Power-out (grey) |
| Protection | Over current, short circuit, thermal protection DC output protection and HF protection (amplifier) |
| Construction | 18mm birch plywood, textured polyurea coating |
| Grille | Custom perforated metal grille with acoustic foam 4 rubber feet, 2 side handles |
| Installation / Rigging / Flying | Ø35mm pole mount socket Prepared for stacking |
| Dimensions (WxDxH) | 590x590x440mm 23.23x23.23x17.32in |
| Weight | 38Kg 83.78lb |