

G1810



This G1810 is on a bass reflex configuration and constructed of 18mm birch plywood featuring a 18" loudspeaker with 4" voice coil delivering a nominal power handling of 1200W rms at 8 Ohms each giving low-ranging yet clearly defined bass response and rendering impulses with great accuracy in a very compact and robust enclosure.



Cena:

Kategorie: [Audio](#), [Scena](#), [Głośniki](#), [Instalacje AV](#),
[Nagłośnienie obiektów](#)

GALLERY IMAGES



OPIS

The BASS-F series offers a professional passive/active flyable subwoofers range becoming the perfect choice for sound reinforcement challenges demanding high SPL and natural-sounding bass response designed to enhance the ultra-low bass of an existing PA system.

A perforated steel grille protects the loudspeaker and there are two side handles as

well as four points in the rear for castors mounting. The enclosure has an integrated rigging system flyware and Ø9.8mm ball pins w/ stainless steel lanyard with PVC to facilitate ease of mounting and there is a metal rigging frame that allows the system to be used ground stacked or individually flown to increase its versatility combined with the LA10 (1x 10" line array speaker).

Key Features

- Bass reflex & flyable PASSIVE subwoofer
- Suited for 10" line array speaker - LA10
- 1x 18" (4in VC) LF EU transducer, 1200W AES
- Versatile, compact and coherent subwoofer
- 2x NL4 connected in parallel
- Optimized for high SPL output
- Made for an impact bass
- Prepared for stacking and flying operation
- Rugged and durable 18mm birch plywood construction
- Powder coated custom perforated steel grille

TECH SPECS

Type	Flyable & compact PASSIVE subwoofer
Enclosure Design	Bass reflex
Power Output (RMS)	1200W (AES)
	2400W (Program)
	4800W (Peak)
Frequency Range	32Hz - 200Hz
Nominal Impedance	8Ohm
Transducer Type	1x 18" LF (4in VC) EU transducer
Crossover Frequency	35Hz Butterworth 18dB (low cut filter)
Max. SPL (peak)	132dB @ 1m
Connector	2x NL4 in parallel
Construction	18mm birch plywood with polyurea coating

Grille	Custom perforated metal grille w/ acoustic foam
	Integrated rigging flyware
Installation / Rigging / Flying	Ø9.8mm ball pins w/ stainless steel lanyard with PVC 2 wood feet, 2 recessed side handles Prepared for castors
Dimensions (WxDxH)	540x740x520mm 21.26x29.13x20.47in
Weight	52Kg 114.64lb