

# G1828



This G1828 is on a bass reflex configuration and constructed of 18mm birch plywood featuring a 18" loudspeaker with 4" voice coil delivering a nominal power handling of 1200W rms at 8 Ohms each giving low-ranging yet clearly defined bass response and rendering impulses with great accuracy in a very compact and robust enclosure.



#### Cena:

**Kategorie:** <u>Audio</u>, <u>Scena</u>, <u>Głośniki</u>, <u>Instalacje AV</u>, Nagłośnienie obiektów

# **GALLERY IMAGES**





#### **OPIS**

The BASS-F series offers a professional passive/active flyable subwoofers range becoming the perfect choice for sound reinforcement challenges demanding high SPL and natural-sounding bass response designed to enhance the ultra-low bass of an existing PA system.

A perforated steel grille protects the loudspeaker and there are two side handles as

well as four points in the rear for castors mounting. The enclosure has an integrated rigging system flyware and  $\emptyset$ 9.8mm ball pins w/ stainless steel lanyard with PVC to facilitate ease of mounting and there is a metal rigging frame that allows the system to be used ground stacked or individually flown to increase its versatility combined with the LA28 (2x 8" line array speaker).

## **Key Features**

- Bass reflex & flyable PASSIVE subwoofer
- Suited for 2x 8" line array speaker LA28
- 1x 18" (4in VC) LF EU transducer, 1200W AES
- Versatile, compact and coherent subwoofer
- 2x NL4 connected in parallel
- Optimized for high SPL output
- Made for an impact bass
- Prepared for stacking and flying operation
- Rugged and durable 18mm birch plywood construction
- Powder coated custom perforated steel grille

# **TECH SPECS**

Type	Flyable & compact PASSIVE subwoofer
1 4 5 5	Tryable a compact Tribbive Sabwooler

Enclosure Design Bass reflex

1200W (AES)

Power Output (RMS) 2400W (Program)

4800W (Peak)

Frequency Range 32Hz - 200Hz

Nominal Impedance 80hm

Transducer Type 1x 18" LF (4in VC) EU transducer

Crossover Frequency 35Hz Butterworth 18dB (low cut filter)

Max. SPL (peak) 132dB @ 1m

Connector 2x NL4 in parallel

Construction 18mm birch plywood with polyurea coating

Grille Custom perforated metal grille w/ acoustic foam

Integrated rigging flyware

Ø9.8mm ball pins w/ stainless steel lanyard with PVC

Installation / Rigging / Flying 2 wood feet, 2 recessed side handles

Prepared for castors Prepared for stacking

640x650x520mm

Dimensions (WxDxH) 25.20x25.59x21.26in

52Kg

Weight 32kg 114.64lb