

I6

The Installation series speakers is the right choice to anyone that wants to install loudspeakers into a wall or into a ceiling matching the high quality sound requirements for modern indoor spaces. Extremely compact, accurate and good looking the 2-way speakers can also be complemented with a number of MOOSE subwoofer systems. This I6 incorporates high quality EU transducer combined with an extremely high sensitivity and lower distortion Kapton 1" driver for outstanding detail and clarity in high frequencies without harshness.



Cena:


Kategorie: Audio, Scena, Głośniki, Instalacje AV, Nagłośnienie obiektów



GALLERY IMAGES







OPIS

Key Features

- 2-way passive installation speakers
- Elegant, refined and lightness design
- 6" (1.26in) FR EU transducer
- High sensitivity 1" HF Kapton driver

- Euroblock terminal
- Optional line transformer, 100V - 8ohm / 15W / 30W power taps
- Prepared for wall/ceiling mounting, 4x M6 inserts for "U" bracket (supplied)
- 4x M5 inserts for Wall mount support adjustable in 2 axes (optional)
- Rugged and durable 12mm birch plywood

TECH SPECS

Type	2-Way passive installation speaker
Enclosure Design	Bass reflex trapezoidal enclosure
Power Output (RMS)	140W (AES) 280W (Program)
Frequency Range	80Hz - 18kHz
Nominal Impedance	8Ohm
Transducer Type	6" FR (1.26in) EU transducer 1" HF (1.00in) Kapton EU transducer
Dispersion	80° conical, aluminum horn
Crossover Frequency	2200Hz
Max. SPL (peak)	116dB @ 1m
Connector	Phoenix Contact® Euroblock speaker terminal I6T: 100V line transformer, 8ohm / 15W / 30W power taps
Construction	12mm brich plywood, black or white finishing
Grille	Custom perforated metal grille w/ acoustic foam
Installation / Rigging / Flying	4x M6 inserts for "U" bracket (supplied) 4x M5 inserts for wall mount/ceiling support, 2-axes (optional)
Dimensions (WxDxH)	190x200x300mm 7.48x7.87x11.81in
Weight	6.0Kg 13.22lb