
The series compromises 3 models, IB 8 with a 8" (1.5in VC), the IB12 with a 12" (2.95in VC) and IB15 with a 15" (4in VC) all equipped with rubber surround EU transducers to provide excellent power density in compact enclosures.

This INSTALL SUB series is the perfect partner to work with MOOSE PURE and CUE series acting as a supplement in PA installations to complete the existing sound with a deep and extended low frequency response, the ideal solution to any installed sound applications where space is limited allows close placement to any wall or



Features:

- Bass reflex installation subwoofer
- Available in passive/active versions
- 1x 15" (4in VC) LF EU transducer
- 1000W AES / 1400W Program power
- 2x NL4 connectors in parallel
- Active version driven by class D amplifier, variable X-over frequency
- Versatile, compact to permit unobtrusive placement
- Supplied with wallmount brackets
- Rugged and durable 15mm birch plywood construction
- Powder coated custom perforated steel grille

430 [16.93] [66] • <u>ق</u> **®**

550 [21.65]

530 [20.87]

Dimensions in mm [in]

Technical specifications:

Acoustical

Туре Compact passive subwoofer

Enclosure design Bass reflex 1000W / 1400W Power rating (RMS/Program) 38 - 160Hz (-10dB) Frequency range

Nominal impedance 8 ohm

Transducer type 1x 15" LF (4in VC) EU transducer

Crossover frequency N/A

SPL (1W/1kHz) 136dB @ 1m (peak) 2x NL4 in parallel Connector

Mechanical

Enclosure 15mm birch plywood, rugged polyurea coating Grille Custom perforated metal grilles w/ acoustic foam

Black or white textured Color

Hardware 4 rubber feet

Wallmount brackets (supplied)

Dimensions 530x550x430mm | 20.87x21.65x16.93in

Weight 29Kg | 63.93lb