IB15

The series compromises 3 models, IB 8 with a 8" (1.5in VC), the IB12 with a 12" (2.95in VC) and IB15 with a 15" (4in VC) all equipped with rubber surround EU transducers to provide excellent power density in compact enclosures.



Cena:

Kategorie: Audio, Scena, Głośniki, Instalacje AV, Nagłośnienie obiektów



GALLERY IMAGES







OPIS

Key Features

- Bass reflex installation subwoofer
- Available in passive/active versions
- 1x 15" (4in VC) LF EU transducer
- 1000W AES / 1400W Program power

- 2x NL4 connectors in parallel
- Versatile, compact to permit unobtrusive placement
- 2 recessed handles on top
- Rugged and durable 15mm birch plywood construction
- Powder coated custom perforated steel grille

TECH SPECS

Type	Compact PASSIVE subwoofer
Enclosure Design	Bass reflex encolsure
Power Output (RMS)	1000W (AES) 1400W (Program) 7000W (Peak)
Frequency Range	38Hz - 160Hz (-10dB)
Nominal Impedance	8 Ohm
Transducer Type	15" (4in VC) LF European transducer
Max. SPL (peak)	130dB @ 1m (continuous) 136dB @ 1m (peak)
Connector	2x NL4 in parallel
Construction	15mm birch plywood with polyurea coating
Grille	Custom perforated metal grille w/ acoustic foam
Installation / Rigging / Flying	4 rubber feet 2 recessed handles on top
Dimensions (WxDxH)	530x550x430mm 20.87x21.65x16.93in
Weight	29Kg 63.93lb