
The series compromises 3 models, IB 8 with a 8" (1.5in VC), the IB12 with a 12" (2.95in VC) and IB15 with a 15" (4in VC) all equipped with rubber surround EU transducers to provide excellent power density in compact enclosures.

This INSTALL SUB series is the perfect partner to work with MOOSE PURE and CUE series acting as a supplement in PA installations to complete the existing sound with a deep and extended low frequency response, the ideal solution to any installed sound applications where space is limited allows close placement to any wall or corner.



## Features:

- Bass reflex installation subwoofer
- Available in passive/active versions
- 1x 8" (1.5in VC) LF EU transducer
- 200W AES / 400 Program power
- 2x NL4 connectors in parallel
- Active version driven by class D amplifier, variable X-over frequency
- Versatile, compact to permit unobtrusive placement
- Supplied with wallmount brackets
- Rugged and durable 15mm birch plywood construction
- Powder coated custom perforated steel grille

## Technical specifications:

## Acoustical

Type Compact passive subwoofer

Enclosure design Bass reflex

Power rating (RMS/Program) 200W / 400W

Frequency range 40 - 160Hz (-10dB)

Nominal impedance 8 ohm

Transducer type 1x 8" LF (1.5in VC) EU transducer

Crossover frequency N/A

SPL (1W/1kHz) 121dB @ 1m (peak)
Connector 2x NL4 in parallel

## Mechanical

Enclosure 15mm birch plywood, rugged polyurea coating
Grille Custom perforated metal grilles w/ acoustic foam


Color Black or white textured

Hardware 4 rubber feet

Wallmount brackets (supplied)

Dimensions 400x215x400mm | 15.75x8.46x15.75in

Weight 11Kg | 24.25lb





Dimensions in mm [in]