IB8

The series compromises 3 models, IB 8 with a 8" (1.5in VC), the IB12 with a 12" (2.95in VC) and IB15 with a 15" (4in VC) all equipped with rubber surround EU transducers to provide excellent power density in compact enclosures.



Cena:
Kategorie: Audio, Scena, Głośniki, Instalacje AV, Nagłośnienie obiektów



GALLERY IMAGES



OPIS

Key Features

- Bass reflex installation subwoofer
- Available in passive/active versions
- 1x 8" (1.5in VC) LF EU transducer
- 200W AES / 400 Program power

- 2x NL4 connectors in parallel
- Active version driven by class D amplifier, variable X-over frequency
- Versatile, compact to permit unobtrusive placement
- Supplied with wallmount brackets
- Rugged and durable 15mm birch plywood construction
- Powder coated custom perforated steel grille

TECH SPECS

Type	Compact PASSIVE subwoofer
Enclosure Design	Bass reflex
Power Output (RMS)	200W (AES) 400W (Program)
Frequency Range	40Hz - 160Hz (-10dB)
Nominal Impedance	8 Ohm
Transducer Type	8" (1.5in VC) LF European transducer
Max. SPL (peak)	115dB @ 1m (continuous) 121dB @ 1m (peak)
Connector	2x NL4 in parallel
Construction	15mm birch plywood with polyurea coating
Grille	Custom perforated metal grille w/ acoustic foam
Installation / Rigging / Flying	4 rubber feet Wallmount brackets (supplied)
Dimensions (WxDxH)	400x215x400mm 15.75x8.46x15.75in
Weight	11Kg 24.25lb