IB8A

This IB8A active version is driven by single channel premium quality EU class D amplifier featuring all electronic circuitry protection, with parallel XLR/M and XLR/F connectors for simple loop-through connectivity and a rotary potentiometer that allows to adjust the X-over frequency easily



Cena:
Kategorie: Audio, Scena, Głośniki, Instalacje AV, Nagłośnienie obiektów



GALLERY IMAGES







OPIS

Key Features

- Bass reflex installation subwoofer
- Active version with premium quality EU amplifier
- 1x 8" (1.5in VC) LF EU transducer
- 320W rms class D, single channel amplifier

- 85-264Vac universal mains, SMPS, all electronic protections
- Variable X-over frequency adjustable by rotary pot
- Supplied with wallmount brackets
- Rugged and durable 15mm birch plywood construction
- Powder coated custom perforated steel grille

TECH SPECS

Type	Compact ACTIVE subwoofer
Enclosure Design	Bass reflex
Power Output (RMS)	200W (AES) 400W (Program)
Frequency Range	40Hz - 160Hz
Nominal Impedance	N/A
Transducer Type	1x 8" LF (1.5in VC) EU transducer
Crossover Frequency	Adjustable by potentiometer, 40Hz - 160Hz
Max. SPL (peak)	115dB @ 1m (continuous) 121dB @ 1m (peak)
Amplifier type	Class D, single channel amplifier
Amplifier output	320W (continuous)
Input	XLR/F 3p connector
Output	XLR/M 3p connector
Indicators	Power on/off
Controls	Master level control, X-over frequency
AC Power Supply	Switch mode power supply, 85-264Vac with PFC
AC mains connector	Neutrik® powerCON, Power-in (blue) / Power-out (grey)
Protection	Over current, short circuit, thermal protection DC output protection and HF protection (amplifier)
Construction	15mm birch plywood, textured polyurea coating
Grille	Custom perforated metal grille w/ acoustic foam
Installation / Rigging / Flying	4 wood feet Prepared for wallmount

Dimensions (WxDxH)	400x215x400mm 15.75x8.46x15.75in
Weight	13Kg 28.67lb