



KI12 SP



Conceived and manufactured to give clients a flexible and easy to use product introduction to Outline, the new Ki series brings the engineering quality, distinctive lines and audio performance that have made the Italian brand an international reference point in sound reinforcement. Both Ki10 SP and Ki12 SP's compact dimensions, audio performance and thoughtful design make them ideal solutions for a wide variety of permanently installed applications.



Cena:

Kategorie: [Audio](#), [Scena](#), [Głośniki](#), [Instalacje AV](#),
[Nagłośnienie obiektów](#)

GALLERY IMAGES



OPIS

Ki10 SP and Ki12 SP self-powered loudspeakers are equipped with 10" and 12" LF

transducers respectively, both of which feature a 2.5" voice coil for high power and reliability. A 1.5" diaphragm compression driver provides the HF reproduction. The Outline-designed passive crossover networks fitted to both models also make them very efficient in terms of amplifier channels and external control.

Both products also feature another Outline first, a brand new design of rotatable waveguide. Many comparable loudspeakers offer this facility but Outline's Ki-series are the first to allow the installer to quickly and easily rotate the entire horn and HF section without any disassembly of the loudspeaker. This piece of original engineering offers a real advantage in small rooms or those with low headroom, as the HF horn can be quickly adjusted to ensure the required dispersion (100° x 50° or 50° x 100°) regardless of the orientation of the cabinet.

The combination of high quality transducers and innovative acoustic design delivers excellent sonic performance and ample power handling, especially considering the Ki-Series' price point. Additionally, the cutting-edge moulding technology used by Outline enables the company to manufacture HF horns that are both rigid and light, bringing benefits in terms of reduced distortion and easier handling.

PERFORMANCE SPECIFICATIONS

Frequency Response (-10 dB)	49 Hz-22 kHz*
Frequency Response (+/-3dB)	71Hz - 21 kHz
Nominal Dispersion	100° x 50° (H x V)
Power Amplifier	Type: Class D (digital) Input impedance: 4.5 kΩ balanced Rated power: 2 x 700 W EIAJ at 8 Ω Cooling: temperature controlled variable speed fan Special feature: four on-board pre-sets, selectable input gain
Maximum SPL Output	132 dB SPL** <i>* with Preset 2** calculated using +10 dB Crest Factor signal @ 1 m, Free Field</i>

PHYSICAL

Component Low	12" woofer
---------------	------------

Component High	1.5" diaphragm compression driver
Loading Low	Bass-reflex
Loading High	Rotatable moulded horn
Connectors	Signal: 1 XLR + 1 Link Out
	USB: Type-B
	Mains: 1 Powercon True1 + 1 Link Out
Cabinet Material	Baltic birch plywood
Cabinet Finish	Black polyurea coating
Grille	Epoxy powder coated
Installation Points	18 x M8 threaded points
Pole Mount	35 mm socket
Handles	1 x Recessed handle on top
Height	575 mm - 22 5/8"
Width	320 mm - 12 5/8"
Depth	340 mm - 13 3/8"
Weight	20 kg - 44.1 lb