



## LA88



Compact vertical line array element designed to provide high performance, detailed highs and a well-defined midrange. The LA88 is a front loaded enclosure that features an internal passive crossover, prepared for bi-amp operation, having built-in premium quality EU transducers (2x 8" - 2in VC) and 2x 1" - 1in VC Neodymium HF drivers, both combinations ensuring powerful and crystal clear reproduction, high SPL with an extended frequency response. The MF/HF pattern is precisely coupled to provide a constant directivity horizontal coverage of 100° thanks to true wave guide horn that ensure consistent and long range projection with very low distortion levels.



**Cena:**

**Kategorie:** [Audio](#), [Scena](#), [Głośniki](#), [Instalacje AV](#),  
[Nagłośnienie obiektów](#)

## GALLERY IMAGES



## OPIS

## Key Features

- Front loaded array element
- Trapezoidal enclosure
- 2x 8" (2in VC) MF + 2x 1" (1in VC) HF EU transducers
- 2x NL4 connected in parallel
- Bi-amp operation
- High performance and crystal clear reproduction
- Faithful dynamic response and great range
- Integrated rigging system for stacked and flown configurations
- Rugged and durable 15mm birch plywood construction
- Powder coated custom perforated steel grille

## TECH SPECS

Type	2-way line array element
Enclosure Design	Trapezoidal array enclosure
Power Output (RMS)	500W (RMS) 960W (Program) 1400W (Peak)
Frequency Range	80Hz - 18kHz (-10dB)
Nominal Impedance	Full Range: 8 ohm LF + MF: 16 ohm HF: 16 ohm
Transducer Type	8" MF (2.0in VC) EU transducer, front loaded 8" MF (2.0in VC) EU transducer, horn loaded 2x 1" HF (1.0in) European transducer
Dispersion	Horizontal: 100° Vertical: 7°
Crossover Frequency	300Hz passive 2.2kHz active or passive Bi-amp operation, user selectable
Max. SPL (peak)	Passive: 124dB (continuous), 130dB (peak) LF + MF: 125dB (continuous), 132dB peak HF: 124dB (continuous), 131dB (peak)



Connector	2x NL4 in parallel
Construction	15mm birch plywood, rugged polyurea coating
Grille	Custom perforated metal grille with acoustic foam
	Integrated rigging flyware
Installation / Rigging / Flying	Splay angle adjustable, 8° (1° increments) Ø9.8mm ball pins w/ stainless steel lanyard with PVC
Dimensions (WxDxH)	640x435x245mm 25.19x17.13x9.65in
Weight	23Kg 50.70lb