



## M15



The GROOVE M15 stage monitor incorporates a 12" (2.5" VC) LF loudspeaker that combines excellent linearity with good sensitivity and power handling characteristics together with a 1" (1.73in) compression driver coupled to a CD rotatable (90°x60° and 60°x90°) horn and an internal passive crossover resulting in a surprising sonic performance inside a compact package.



**Cena:**

**Kategorie:** [Audio](#), [Scena](#), [Głośniki](#), [Instalacje AV](#),  
[Nagłośnienie obiektów](#)

## GALLERY IMAGES



## OPIS

### Key Features

- Multipurpose 2-way stage monitor
- Bass reflex wedged enclosure

- 15" (2.5in VC) MF + 1" (1.73in VC) HF EU transducers
- User-rotatable CD horn 90°x60° for ideal dispersion
- 2x NL4 connected in parallel
- Pole mount socket for stand support
- Elegant looking professional enclosure
- Rugged and durable 15mm birch plywood, polyurea coating

## TECH SPECS

|                                 |                                                                    |
|---------------------------------|--------------------------------------------------------------------|
| Type                            | 2-Way passive monitor                                              |
| Enclosure Design                | Wedged cabinet - bass reflex                                       |
| Power Output (RMS)              | 410W (RMS)<br>560W (Program)<br>1100W (Peak)                       |
| Frequency Range                 | 50Hz - 19kHz                                                       |
| Nominal Impedance               | 8Ohm                                                               |
| Crossover Frequency             | 2000Hz                                                             |
| Transducer Type                 | 15" MF (2.5in VC) EU transducer<br>1" HF (1.73in VC) EU transducer |
| Dispersion                      | CD horn, 90°x60° and 60°x90°<br>User-rotatable                     |
| Max. SPL (peak)                 | 127dB @ 1m                                                         |
| Construction                    | 15mm birch plywood, textured polyurea coating                      |
| Grille                          | Custom perforated metal grille with acoustic foam                  |
| Installation / Rigging / Flying | 4 rubber feet<br>Ø35mm pole mount socket                           |
| Dimensions (WxDxH)              | 750x540x360mm<br>29.53x21.26x14.17in                               |
| Weight                          | 25Kg<br>55.16lb                                                    |

