M15

The GROOVE M15 stage monitor incorporates a 12" (2.5" VC) LF loudspeaker that combines excellent linearity with good sensitivity and power handling characteristics together with a 1” (1.73in) compression driver coupled to a CD rotatable (90°x60° and 60°x90°) horn and an internal passive crossover resulting in a surprising sonic performance inside a compact package.



Cena:
Kategorie: Audio, Scena, Głośniki, Instalacje AV, Nagłośnienie obiektów



GALLERY IMAGES











OPIS

Key Features

- Multipurpose 2-way stage monitor
- Bass reflex wedged enclosure
- 15" (2.5in VC) MF + 1" (1.73in VC) HF EU transducers
- User-rotatable CD horn 90°x60° for ideal dispersion
- 2x NL4 connected in parallel
- Pole mount socket for stand support
- Elegant looking professional enclosure
- Rugged and durable 15mm birch plywood, polyurea coating

TECH SPECS

Type	2-Way passive monitor
Enclosure Design	Wedged cabinet - bass reflex
Power Output (RMS)	410W (RMS) 560W (Program) 1100W (Peak)
Frequency Range	50Hz - 19kHz
Nominal Impedance	8Ohm
Crossover Frequency	2000Hz
Transducer Type	15" MF (2.5in VC) EU transducer 1" HF (1.73in VC) EU transducer
Dispersion	CD horn, 90°x60° and 60°x90° User-rotatable
Max. SPL (peak)	127dB @ 1m
Construction	15mm birch plywood, textured polyurea coating
Grille	Custom perforated metal grille with acoustic foam

Installation / Rigging / Flying	4 rubber feet Ø35mm pole mount socket
Dimensions (WxDxH)	750x540x360mm 29.53x21.26x14.17in
Weight	25Kg 55.16lb