MA10

The GROOVE MA10 stage monitor incorporates a 10" (2" VC) LF loudspeaker that combines excellent linearity with good sensitivity and power handling characteristics together with a 1” (1.73in) compression driver coupled to a CD rotatable (90°x60° and 60°x90°) horn and an internal passive crossover resulting in a surprising sonic performance inside a compact package.



Cena:
Kategorie: Audio, Scena, Głośniki, Instalacje AV, Nagłośnienie obiektów



GALLERY IMAGES











OPIS

Key Features

- Multipurpose wedged stage monitor
- Passive and active versions available
- 10" (2in VC) MF + 1" (1.73in VC) HF EU transducers
- User-rotatable CD horn 90°x60° for ideal dispersion
- Driven by a Class D, 2 channel amplifier
- NL4 output to drive a passive monitor
- Pole mount socket for stand support
- Elegant looking professional enclosure
- Rugged and durable 15mm birch plywood

TECH SPECS

Type	2-Way active monitor
Enclosure Design	Wedged cabinet - bass reflex
Power Output (RMS)	360W (RMS) 510W (Program) 900W (Peak)
Frequency Range	80Hz - 19kHz
Nominal Impedance	N/A
Transducer Type	10" MF (2in VC) EU transducer 1" HF (1.73in VC) EU transducer
Dispersion	CD horn, 90°x60° and 60°x90° User-rotatable
Crossover Frequency	DSP controlled with selectable presets 48KHz sampling frequency 24 bit AD/DA converter
Max. SPL (peak)	122dB @ 1m
Amplifier type	Class D, 2 channel amplifier

Amplifier output	800W + 400W (continuous) 1500W (peak)
Input	XLR/jack combo connector
Output	XLR/M 3p
Indicators	Power, signal/preset, clip
Controls	Master level control, 4 selectable presets
Feature	Cooling by convection
AC Power Supply	Switching power supply, 85-264Vac
AC mains connector	Neutrik® powerCON, Power-in (blue) / Power-out (grey)
Protection	Over current and short circuit protection, thermal protection, DC output protection and HF protection (amplifier)
Construction	15mm birch plywood, textured polyurea coating
Grille	Custom perforated metal grille with acoustic foam
Installation / Rigging / Flying	4 rubber feet Ø35mm pole mount
Dimensions (WxDxH)	500x440x350mm 19.69x17.32x13.78in
Weight	21Kg 46.29lb