ONE.SL12

Weatherproof direct-radiating 12" two-way system with 60 x 40 HF coverage in rotomolded HDPE enclosure. 400 watts continuous power handling. 55– 18,000 Hz frequency response. 8-ohm operation. IP 55 weather rated. Input weather cover with IP 68-rated gland nut. Net weight 26 kg / 57.3 lbs.



Cena:
Kategorie: Audio, Scena, Głośniki, Instalacje AV, Nagłośnienie obiektów

GALLERY IMAGES



OPIS

ONE.SL12 SILVER SERIES LOUDSPEAKERS

SPECIFICATIONS:

- Frequency Response: 55 - 18,000 Hz + 3 dB
- Input Connection: Barrier strip
- Frequency Range: 45 - 20,000 Hz -10 dB
- LF Transducer: 12 in / 305 mm with 3 in voice coil
- Power Handling: 400 watts continuous; 800 watts program1,600 watts peak/
- * NOTE: All system power handling ratings Net Weight: 26 kg / 57.3 lb
  are amplifier headroom dependent Direct Weather Performance: IEC 60529
- Dimensions (H x W x D), in: 28.3 x 17.6 x 14.7 in
- Dimensions (H x W x D), mm: 719.7 x 448.2 x 372.2 mm
- HF Transducer: 2.5 in / 63 mm with titanium diaphragm
- Sensitivity (1 watt @1 meter): 98 dB Finish: Gray
- Calculated Output Capability: 124 dB continuous / 130 dB peak
- Recommended High-Pass: 55 Hz, 24 dB Butterworth