ONE.SL15

Weatherproof direct-radiating 15" two-way system with 60 x 40 HF coverage in rotomolded HDPE enclosure. 500 watts continuous power handling. 50– 18,000 Hz frequency response. 8-ohm operation. IP 55 weather rated. Input weather cover with IP 68-rated gland nut. Net weight 35 kg / 77.2 lb.





Cena:
Kategorie: Audio, Scena, Głośniki, Instalacje AV, Nagłośnienie obiektów

GALLERY IMAGES



OPIS

ONE.SL15 SILVER SERIES LOUDSPEAKERS

SPECIFICATIONS:

- Frequency Response: 50 - 18,000 Hz + 3 dB
- Input Connection: Barrier strip
- Frequency Range: 40 - 20,000 Hz -10 dB
- LF Transducer: 15 in / 381 mm with 3 in voice coil
- Power Handling: 500 watts continuous
  1,000 watts program Dimensions (H x W x D), mm: 779.7 x 513.2 x 422.2 mm
  2,000 watts peak * Dimensions (H x W x D), in: 30.7 x 20.2 x 16.6 in
  NOTE: All system power handling ratings are Net Weight: 35 kg / 77.2 lb
  amplifier headroom dependent Direct Weather Performance: IEC 60529 / IP 55
- HF Transducer: 2.5 in / 63 mm with titanium diaphragm
- Sensitivity (1 watt @1 meter): 100 dB
- Finish: Gray
- Calculated Output Capability: 126 dB continuous / 132 dB peak
- Recommended High-Pass: 50 Hz, 24 dB Butterworth
- Nominal Impedance: 8 ohms

Optional Accessories:

- Pole Mount Bracket: SL.PMT