

PD4

Pure Resonance Audio PD4 4" 2-Way Open-Ceiling Pendant Mount Loudspeaker

DESCRIPTION:

Designed to meet the needs of indoor and outdoor open -ceiling commercial applications, the Pure Resonance Audio PD4 4" full-range pendant speaker is weather-resistant, high powered and easy to install. This 70-volt pendant mount loudspeaker is perfect for restaurants, retail stores, offices, warehouses, or any other open-architecture high ceiling environment where paging, announcements or foreground and background music is required.

FEATURES:

- \cdot Durable weather resistant construction
- \cdot 70.7V/100V operation for commercial applications
- \cdot Tap settings:
 - 70.7V: 2W / 4W / 8W / 16W / 8 ohm
 - 100V: 4W / 8W / 16W / 8 ohm
- $\cdot\,$ Includes pendant mounting hardware
- Surface-mount and ground stake accessory kits sold separately
- Ideally suited for such applications as background music (BGM) and paging



PRODUCT SPECIFICATIONS:

Power Handling	25W RMS; 70W Peak
Frequency Response (±3 dB)	95 Hz - 20 KHz
Frequency Response (±10 dB)	65 Hz – 20 kHz
Sensitivity	85 dB 1m/1w
Impedance	8 Ohm
Peak Output	103 dB
Woofer	4 inch Polypropylene
Tweeter	3/4 inch Black silk
Transformer	70.7V: 4W / 8W / 16W / 32W / 8 ohm 100V: 8W / 16W / 32W / 8 ohm
Connections	Four-pin Euroblock
Grill	Baked black aluminum
Certifications	REACH, RoHS
Dimensions (H x Dia)	7" (177.8 mm) x 5" (127 mm)
Shipping Dimensions (H x W x D)	8.27" (210 mm) x 8.98" (228 mm) x 6.81" (173 mm)
Weight	3.35 lbs (1.52 kg)
Shipping Weight	4.63 lbs (2.10 kg)