

PD6

Pure Resonance Audio PD6 6.5" 2-Way Open-Ceiling
Pendant Mount Loudspeaker

DESCRIPTION:

Designed to meet the needs of indoor and outdoor open-ceiling commercial applications, the Pure Resonance Audio PD6 6.5" full-range pendant speaker is weather-resistant, high powered and easy to install. This 70-volt pendant mount loudspeaker is perfect for restaurants, retail stores, offices, warehouses, or any other open-architecture high ceiling environment where paging, announcements or foreground and background music is required.

FEATURES:

- Durable weather resistant construction
- Power tap transformer switch for selectable 8 ohm or 70V/100V operation for commercial applications
- Tap settings:
 - 70V: 8 ohm, 4W, 8W, 16W, 32W
 - 100V: 8 ohm, 8W, 16W, 32W
- Includes pendant mounting hardware
- Surface-mount and ground stake accessory kits sold separately
- Ideally suited for such applications as background music (BGM) and paging



PRODUCT SPECIFICATIONS:

Power Handling	30 Watts RMS; 70 Watts Peak
Frequency Response (± 3 dB)	95Hz - 20KHz
Frequency Response (± 10 dB)	65 Hz – 20 kHz
Sensitivity	87dB 1m/1w
Impedance	8 Ohm
Peak Output	103dB
Woofer	6.5 inch Polypropylene
Tweeter	1 inch Black silk
Transformer	70.7V: 4W / 8W / 16W / 32W / 8 ohm 100V: 8W / 16W / 32W / 8 ohm
Connections	Four-pin Euroblock
Grill	Baked black aluminum
Certifications	REACH, RoHS
Dimensions (H x Dia)	10.3" (285 mm) x 8.1" (207 mm)
Weight	6.35 lbs (2.88 kg)
Shipping Weight	8.33 lbs (3.78 kg)