SUB 110 SP

SUB 110 SP (the **self-powered version** of the SUB 110 enclosure) has been designed for venues where low frequencies are needed but discrete placement is required. The maximum available power from the amplifier module is 700 W EIAJ at 8 ohm (2800 W peak). SUB 110 SP can faithfully reproduce the lower frequencies down to 39 Hz and up to a peak SPL of 132.5 dB.



Cena:
Kategorie: Audio, Scena, Głośniki, Instalacje AV, Nagłośnienie obiektów



GALLERY IMAGES





OPIS

Features

- Highly efficient, self-powered ultra-compact subwoofer fitted with one 10” transducer
- Integrated 700 W EIAJ at 8 ohm (2800 W peak) amplifier module
- Exceptional size-to-power ratio (132.5 dB SPL short-term peak @ 1 m)
- Deep, very clean low frequencies – previously available only from much larger cabinets
- Extremely compact cabinet – can be easily tucked under bench seating
- Flying points (M6 thread) and very low weight
- Finished with Polyurea, featuring amazing durability and superior physical properties
- Conceived, designed and manufactured exclusively in Italy (as are all Outline products)

Applications

- High quality installations in houses of worship, clubs, lounge bars, live music-venues, theatres, conference rooms, stores, and shopping centres. Also suitable for high quality mobile applications, industrial and corporate rental companies
- An ideal partner for all Outline compact point-source systems such as Vegas 24, Vegas 6.5, Vegas 8 CX, DVS 8

PERFORMANCE SPECIFICATIONS

Frequency Response -10 dB	39 Hz – 100 Hz (preset 1: standard)
Nominal Dispersion	Quasi-Omnidirectional
Power amplifier	Type: Class D (digital) Input impedance: 4.5 kΩ balanced Rated power: 700 W EIAJ at 8 Ω Cooling: temperature controlled variable speed fan Special feature: four on-board presets, selectable input gain
Maximum SPL Output *	132.5 dB SPL (preset 1: standard)

* *calculated using +10 dB Crest Factor signal @ 1 m, Half space*

PHYSICAL

Component	1 x 10” – Dual Reflex Band Pass
Connectors	Signal: 1 XLR + 1 Link Out Mains: IEC C14 Socket
Cabinet Material	Baltic birch plywood
Cabinet Finish	Black polyurea coating
Grille	Epoxy powder coated
Installation Points	12 x M6 threaded points
Pole Mount	1 x M20 threaded point
Height	258 mm – 10 1/8”
Width	500 mm – 19 5/8”
Depth	550 mm – 21 5/8”
Weight	22 kg – 48.5 lb