

## SUB 110



**SUB 110** has been designed for venues where low frequencies are needed but discrete placement is required. The compact nature of this cabinet allows installation within the tightest of places. Based on a dual-port band-pass design and utilising a single 10" drive-unit, the SUB 110 enclosure can faithfully reproduce the lower frequencies down to 39 Hz and up to a peak SPL of 132.5 dB.



**Cena:**

**Kategorie:** [Audio](#), [Scena](#), [Głośniki](#), [Instalacje AV](#),  
[Nagłośnienie obiektów](#)

## OPIS

### Features

- Highly efficient, powerful low-frequency loudspeaker fitted with one 10" transducer
- Exceptional size-to-power ratio (132.5 dB SPL short-term peak @ 1 m)
- Deep, very clean low frequencies – previously available only from much larger cabinets
- Extremely compact cabinet – can be easily tucked under bench seating
- Flying points (M6 thread) and very low weight
- Finished with Polyurea, featuring amazing durability and superior physical properties
- Conceived, designed and manufactured exclusively in Italy (as are all Outline products)

## Applications

- High quality installations in houses of worship, clubs, lounge bars, live music-venues, theatres, conference rooms, stores, and shopping centres. Also suitable for high quality mobile applications, industrial and corporate rental companies
- An ideal partner for all Outline compact point-source systems such as Vegas 24, Vegas 6.5, Vegas 8 CX, DVS 8

## PERFORMANCE SPECIFICATIONS

Frequency Response -10 dB	39 Hz – 100 Hz (standard preset)
Suggested Cross-Over	max 120 Hz
Nominal Dispersion	Quasi-Omnidirectional
Impedance (Nom/Min)	8 $\Omega$ / 6.1 $\Omega$
Watt AES (Continuous/Peak)	350 W / 1400 W
Maximum SPL Output *	132.5 dB SPL (standard preset)

*\* calculated using +10 dB Crest Factor signal @ 1 m, Half space*

## PHYSICAL

Component	1 x 10" – Dual Reflex Band Pass
Connectors	2 x NL4 Pins 1+/1-
Cabinet Material	Baltic birch plywood
Cabinet Finish	Black polyurea coating
Grille	Epoxy powder coated
Installation Points	12 x M6 threaded points
Pole Mount	1 x M20 threaded point
Height	258 mm – 10 1/8"
Width	500 mm – 19 5/8"
Depth	550 mm – 21 5/8"
Weight	21 kg – 46.3 lb