SUB 110

SUB 110 has been designed for venues where low frequencies are needed but discrete placement is required. The compact nature of this cabinet allows installation within the tightest of places. Based on a dual-port band-pass design and utilising a single 10” drive-unit, the SUB 110 enclosure can faithfully reproduce the lower frequencies down to 39 Hz and up to a peak SPL of 132.5 dB.



Cena:
Kategorie: Audio, Scena, Głośniki, Instalacje AV, Nagłośnienie obiektów



OPIS

Features

- Highly efficient, powerful low-frequency loudspeaker fitted with one 10” transducer
- Exceptional size-to-power ratio (132.5 dB SPL short-term peak @ 1 m)
- Deep, very clean low frequencies – previously available only from much larger cabinets
- Extremely compact cabinet – can be easily tucked under bench seating
- Flying points (M6 thread) and very low weight
- Finished with Polyurea, featuring amazing durability and superior physical properties
- Conceived, designed and manufactured exclusively in Italy (as are all Outline products)

Applications

- High quality installations in houses of worship, clubs, lounge bars, live music-venues, theatres, conference rooms, stores, and shopping centres. Also suitable for high quality mobile applications, industrial and corporate rental companies
- An ideal partner for all Outline compact point-source systems such as Vegas 24, Vegas 6.5, Vegas 8 CX, DVS 8

PERFORMANCE SPECIFICATIONS

Frequency Response -10 dB	39 Hz – 100 Hz (standard preset)
Suggested Cross-Over	max 120 Hz
Nominal Dispersion	Quasi-Omnidirectional
Impedance (Nom/Min)	8 Ω / 6.1 Ω
Watt AES (Continuous/Peak)	350 W / 1400 W

Maximum SPL Output *	132.5 dB SPL (standard preset)

** calculated using +10 dB Crest Factor signal @ 1 m, Half space*

PHYSICAL

Component	1 x 10” – Dual Reflex Band Pass
Connectors	2 x NL4 Pins 1+/1-
Cabinet Material	Baltic birch plywood
Cabinet Finish	Black polyurea coating
Grille	Epoxy powder coated
Installation Points	12 x M6 threaded points
Pole Mount	1 x M20 threaded point
Height	258 mm – 10 1/8”
Width	500 mm – 19 5/8”
Depth	550 mm – 21 5/8”
Weight	21 kg – 46.3 lb