TL 120D

Public address amplifier designed and developped for fixed installations. There are 2 versions available with different output powers, 120W and 220W rms, prepared for rack 19" mounting. Both TL120D and TL200D feature four balanced microphone inputs plus two line inputs in RCA connector, low impedance (4-16Ohm) and high impedance (100V) outputs both in screw terminals. A built-in phantom power supply with on/off push switch is available as well as a priority microphone input in DIN 5p connector. Additionally, both models feature Slave & REC outputs in RCA connectors, 2-band equalizer and MASTER level control making of this TL120D and TL200D the perfect solution for all kind of public address installations.



Cena:

Kategorie: Audio, Scena, Wzmacniacze mocy, Instalacje AV, Wzmacniacze mocy i procesory DSP



GALLERY IMAGES





OPIS

Key Features

- High quality PA amplifier
- Installation PA mixer-amplifier
- 4 Microphone inputs and 1 Line input
- XLR 3p balanced, Euroblock inputs

- 4-16 ohm & constant-voltage outputs (70V and 100V)
- Bass and Teble tone controls
- Ding-dong and Priority muting by VOX
- Built-in electronic protection circuitry
- Solid construction for 19” rack - 2U mounting

TECH SPECS

Type	PA mixer-amplifier
Power Output (RMS)	120W
Frequency Range	50Hz - 14kHz
T.H.D. (20Hz - 20kHz)	< 1% @ 1kHz
Signal-to-noise ratio	> 90 dB @ 1 kHz
Zones	No
Controls	Bass and Treble, Master, Volume for MIC and Line in
Indicators	Power on, Signal and Clip
Inputs	Microphone, XLR/F 3p Euroblock terminals Line in
Outputs	4Ω, 8Ω and 100V line, AUX
Connectors	Input: 6.3mm Jack, RCA line Output: Touch-proof binding posts
Phantom Power	+48V DC
Other Features	Ding-dong, priority MIC, MIC3/LINE3 and MIC4/LINE4 switch
Protections	Short circuit, thermal overload
Operation Voltage	230V AC (factory config.), 50–60 Hz
Power Consumption	150VA
Cooling	Continuously speed fan, 80mm / 230V AC
Dimensions (WxHxD)	2RU spaces, 345mm depth
Weight	11Kg 24.25lb