TL 500P

The Mono channel public address amplifier with a power up to 500W rms. The TL500P features a single channel input performed using a balanced Jack 6.5mm with individual volume control on the real panel. The output signal is available on 2 low impedance outputs in 40hm and 80hm and 2 high impedance outputs in 75V and 100V using block terminals on the rear panel. It is equipped with an advanced protection circuit which protects against short-circuit and overload when necessary. The TL500 is suited for public address fixed installations where a capable and reliable device is needed, also offering a pre-out (LINK) available to connect another amplifier.



Cena:

Kategorie: Audio, Scena, Wzmacniacze mocy, Instalacje AV, Wzmacniacze mocy i procesory DSP



GALLERY IMAGES





OPIS

Key Features

- High quality PA amplifier
- Installation PA mono amplifier
- 3p XLR signal input and 3p XLR signal output
- RCA REC output and RCA LINK output

- 4-8 ohm & constant-voltage outputs (70V and 100V)
- Master volume control on the front panel
- Built-in electronic protection circuitry
- Solid construction for 19” rack - 3U mounting

TECH SPECS

Type	PA mono power amplifier
Power Output (RMS)	500W
Frequency Range	50Hz - 14kHz
T.H.D. (20Hz - 20kHz)	< 1% @ 1kHz
Signal-to-noise ratio	> 90 dB @ 1 kHz
Zones	No
Indicators	Power on
Inputs	Signal in
Outputs	4Ω, 8Ω, 75V and 100V line, REC
Connectors	Input: 6.3mm Jack unb., RCA Output: Jack & RCA
Other Features	Input level adjustment
Protections	Short circuit, thermal overload
Operation Voltage	230V AC (factory config.), 50–60 Hz
Power Consumption	500VA
Cooling	Continuously speed fan, 120mm / 230V AC
Dimensions (WxHxD)	4RU spaces, 370mm depth (14.57in)
Weight	20Kg 44.09lb