

## TL 6Z



Public address amplifier with 6 independent channels/inputs delivering each input 150W rms. This amplifier features 6 independent balanced audio inputs with independent volume controls on the front panel, each input in Jack 6.5mm and 6 outputs in high impedance 100V line transformer with binding-post. It is equipped with an advanced protection circuit which protects against DC short circuit and overload when necessary for better performance on both fixed and mobile public address installations, being the perfect choice for supermarkets, warehouses, medical centres, etc, where there is a need to control each zone independently.



**Cena:**

**Kategorie:** [Audio](#), [Scena](#), [Wzmacniacze mocy](#), [Instalacje AV](#), [Wzmacniacze mocy i procesory DSP](#)

## GALLERY IMAGES



## OPIS

### Key Features

- High quality PA amplifier

- Multizone installation PA amplifier
- XLR 3p balanced, Euroblock inputs
- Constant-voltage outputs (100V)
- Independent zone control (six)
- Individual volume control on the front panel
- Built-in electronic protection circuitry
- Solid construction for 19" rack - 3U mounting

## TECH SPECS

|                       |                                                                                  |
|-----------------------|----------------------------------------------------------------------------------|
| Type                  | Multizone PA mixer/amplifier                                                     |
| Power Output (RMS)    | 6x 150W                                                                          |
| Frequency Range       | 50Hz - 15kHz                                                                     |
| T.H.D. (20Hz - 20kHz) | < 1% @ 1kHz                                                                      |
| Signal-to-noise ratio | > 90 dB @ 1 kHz                                                                  |
| Zones                 | 6 zones                                                                          |
| Controls              | Input channel volume                                                             |
| Indicators            | Power on                                                                         |
| Inputs                | Signal in                                                                        |
| Outputs               | 100V line                                                                        |
| Connectors            | Microphone, XLR/F 3p<br>Euroblock terminals<br>Output: Touch-proof binding posts |
| Other Features        | Independent zone control                                                         |
| Protections           | Short circuit, DC protection                                                     |
| Operation Voltage     | 230V AC (factory config.), 50-60 Hz                                              |
| Power Consumption     | 900VA                                                                            |
| Cooling               | Continuously speed fan, 120mm / 230V AC                                          |
| Dimensions (WxHxD)    | 3RU spaces, 440mm depth (17.32in)                                                |
| Weight                | 23Kg<br>50.71lb                                                                  |

