TL 6Z

Public address amplifier with 6 independent channels/inputs delivering each input 150W rms. This amplifier features 6 independent balanced audio inputs with independent volume controls on the front panel, each input in Jack 6.5mm and 6 outputs in high impedance 100V line transformer with binding-post. It is equipped with an advanced protection circuit which protects against DC short circuit and overload when necessary for better performance on both fixed and mobile public address installations, being the perfect choice for supermarkets, warehouses, medical centres, etc, where there is a need to control each zone independently.



Cena:

Kategorie: Audio, Scena, Wzmacniacze mocy, Instalacje AV, Wzmacniacze mocy i procesory DSP



GALLERY IMAGES





OPIS

Key Features

- High quality PA amplifier
- Multizone installation PA amplifier
- XLR 3p balanced, Euroblock inputs
- Constant-voltage outputs (100V)

- Independent zone control (six)
- Individual volume control on the front panel
- Built-in electronic protection circuitry
- Solid construction for 19” rack - 3U mounting

TECH SPECS

Type	Multizone PA mixer/amplifier
Power Output (RMS)	6x 150W
Frequency Range	50Hz - 15kHz
T.H.D. (20Hz - 20kHz)	< 1% @ 1kHz
Signal-to-noise ratio	> 90 dB @ 1 kHz
Zones	6 zones
Controls	Input channel volume
Indicators	Power on
Inputs	Signal in
Outputs	100V line
Connectors	Microphone, XLR/F 3p Euroblock terminals Output: Touch-proof binding posts
Other Features	Independent zone control
Protections	Short circuit, DC protection
Operation Voltage	230V AC (factory config.), 50–60 Hz
Power Consumption	900VA
Cooling	Continuously speed fan, 120mm / 230V AC
Dimensions (WxHxD)	3RU spaces, 440mm depth (17.32in)
Weight	23Kg 50.71lb