G212

This G212 is built on a 5th order band-pass design equipped with 2x 12" (4in) LF transducers capable of delivering 1400W AES (2800W program), chosen to provide clean, undistorted low frequency reproduction at very high sound pressure levels and able to withstand high power levels without damage with a solid punch.

Cena:
Kategorie: Audio, Scena, Głośniki, Instalacje AV, Nagłośnienie obiektów

GALLERY IMAGES

OPIS

The BASS series offers a professional and compact passive and active subwoofers range becoming the perfect choice for sound reinforcement challenges demanding high SPL and natural sounding bass response designed to enhance the ultra-low bass of an existing PA system.

Key Features

- 5th order Band-Pass Subwoofer
- 2x 12" (4in VC) LF EU transducers
- 1400W (AES) / 2800W (Program) power
- Versatile, compact, coherent and powerful subwoofer
- 2x NL4 connected in parallel
- Optimized for high SPL output
- Prepared for stacking and pole mount usage
- Rugged and durable 18mm birch plywood construction
- Powder coated custom perforated steel grille

TECH SPECS

Type	Compact PASSIVE subwoofer
Enclosure Design	5th order Band-Pass Subwoofer
Power Output (RMS)	1400W (AES) 2800W (Program)
Frequency Range	35Hz - 200Hz (-6dB)
Nominal Impedance	4 Ohm
Transducer Type	2x 12" LF (4in VC) EU transducer
Max. SPL (peak)	129dB @ 1m (continuous) 135dB @ 1m (peak)
Construction	15mm birch plywood with polyurea coating
Grille	Custom perforated metal grille w/ acoustic foam
Installation / Rigging / Flying	4 rubber feet, 2 side handles Ø35mm pole mount socket Prepared for stacking, recesses on top
Dimensions (WxDxH)	600x710x440mm 23.62x27.95x17.32in
Weight	47Kg 103.62lb